



**Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)**

05

001MRZI

EN 14411:2012

**Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$,
for internal and external walls and floorings**

Reaction to fire	Class A1 _{FL} /A1
Breaking strength	Thickness <7,5 mm Breaking strength ≥ 700 N Thickness $\geq 7,5$ mm Breaking strength ≥ 1300 N
Slipperiness	See table attached
Durability, for: - Internal use - External use: Freeze/thaw resistance	Passed Passed
Resistance to thermal shock	Passed



**Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)**

05

002MRZI

EN 14411:2012

**Dry-pressed ceramic tiles, with water absorption $0,5\% < E_b \leq 3\%$,
for internal and external walls and floorings**

Reaction to fire	Class A1 _{FL} /A1
Breaking strength	Thickness <7,5 mm Breaking strength ≥ 700 N Thickness $\geq 7,5$ mm Breaking strength ≥ 1100 N
Durability, for: - Internal use - External use: Freeze/thaw resistance	Passed Passed
Resistance to thermal shock	Passed



**Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)**


05


003MRZI


EN 14411:2012


**Dry-pressed ceramic tiles, with water absorption $3% < E_b \leq 6%$,
for internal walls and floorings**


Reaction to fire	Class A1 _{FL} /A1
Breaking strength	Thickness <7,5 mm Breaking strength ≥600 N Thickness ≥7,5 mm Breaking strength ≥1000 N
Durability, for: -Internal use	Passed


	
<p>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO)</p> <p>05</p> <p>004MRZI</p>	
<p>EN 14411:2012</p> <p>Dry-pressed ceramic tiles, with water absorption $6% < E_b \leq 10%$, for internal walls</p>	
Reaction to fire	Class A1
Durability, for: - Internal use	Passed


	
<p>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO)</p> <p>05</p> <p>005MRZI</p>	
<p>EN 14411:2012</p> <p>Dry-pressed ceramic tiles, with water absorption $E_b > 10%$, for internal walls</p>	
Reaction to fire	Class A1
Durability, for: - Internal use	Passed


	
<p>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO)</p> <p>05</p> <p>006MRZI</p>	
<p>EN 14411:2012</p> <p>Dry-pressed ceramic tiles, with water absorption $3% < E_b \leq 6%$, for internal walls</p>	
Reaction to fire	Class A1
Durability, for: - Internal use	Passed

	
<p>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO)</p> <p>05</p> <p>007MRZI</p>	
<p>EN 14411:2012</p> <p>Dry-pressed ceramic tiles, with water absorption $E_b > 10%$, for internal walls and floorings</p>	
Reaction to fire	Class A1 _{FL} /A1
Breaking strength	Thickness <7,5 mm Breaking strength ≥ 200 N Thickness $\geq 7,5$ mm Breaking strength ≥ 600 N
Durability, for: - Internal use	Passed

	
<p>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO)</p> <p>05</p> <p>008MRZI</p>	
<p>EN 14411:2012</p> <p>Extruded ceramic tiles, with water absorption $E_b \leq 0,5\%$, for internal and external walls and floorings</p>	
Reaction to fire	Class A1 _{FL} /A1
Breaking strength	Thickness <7,5 mm Breaking strength ≥ 600 N Thickness $\geq 7,5$ mm Breaking strength ≥ 1300 N
Durability, for: - Internal use - External use: Freeze/thaw resistance	Passed Passed
Resistance to thermal shock	Passed

	
<p>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO)</p> <p>05</p> <p>009MRZI</p>	
<p>EN 14411:2012</p> <p>Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$, for internal and external walls</p>	
Reaction to fire	Class A1
Durability, for: - Internal use - External use: Freeze/thaw resistance	Passed Passed
Resistance to thermal shock	Passed

	
<p>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO)</p> <p>05</p> <p>010MRZI</p>	
<p>EN 14411:2012</p> <p>Dry-pressed ceramic tiles, with water absorption $0,5% < E_b \leq 3%$, for internal and external walls and floorings</p>	
Reaction to fire	Class A1
Durability, for:	
- Internal use	Passed
- External use: Freeze/thaw resistance	Passed
Resistance to thermal shock	Passed

	
<p>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO)</p> <p>05</p> <p>011MRZI</p>	
<p>EN 14411:2012</p> <p>Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5%$, for internal walls</p>	
Reaction to fire	Class A1
Durability, for:	
- External use: Freeze/thaw resistance	Passed
Resistance to thermal shock	Passed